

Gen-Set Model	Engine Brand	Engine Model	Prime Power (KVA/KW)		Standby Power (KVA/KW)		Fuel Consumption L/h (75%/100% Prime Power)		Governor	of Cylinder	Displacement	Compression Ratio	Injection	Aspiration	Lubrication Capacity (L)	Coolant Capacity (L)
			50Hz-1500RPM	60Hz-1800RPM	50Hz-1500RPM	60Hz-1800RPM	50Hz-1500RPM	60Hz-1800RPM								
DE-L7.5	LISTER	LPW2	7.0/5.6	8.6/6.9	7.6/6.1	9.5/7.6	1.5/1.9	1.8/2.3	M	2L	0.93	18.5:1	D	N	3	6.1
DE-L12.5		LPW3	10.9/8.7	13.3/10.6	12.0/9.6	14.6/11.7	2.2/2.8	2.7/3.4	M	3L	1.395	18.5:1	D	N	3.75	6.5
DE-L17.5		LPW4	15.0/12.0	18.5/14.8	16.5/13.2	20.3/16.2	2.9/3.8	3.6/4.6	M	4L	1.86	18.5:1	D	N	5.5	7.0
DE-P9	PERKINS	403A-11G1	9.0/7.2	11.3/9.0	9.9/7.9	12.4/9.9	2.0/2.6	2.3/3.2	M	3L	1.131	23.0:1	I	N	4.9	5.2
DE-P13		403A-15G1	13.0/10.4	15.8/12.6	14.3/11.4	17.4/13.9	3.7/4.1	3.4/4.4	M	3L	1.496	22.5:1	I	N	6.0	6.0
DE-P20		404D-22G	20.3/16.2	24.2/19.3	22.3/17.8	26.6/21.3	5.3/6.1	4.8/6.2	M	4L	2.216	23.3:1	I	N	10.6	7.0
DE-P30		1103A-33G	30.0/24.0	34.9/27.9	33.0/26.4	38.2/30.6	5.4/7.1	6.6/8.6	M	3L	3.3	19.25:1	D	N	7.9	10.2
DE-P45		1103A-33TG1	45.0/36.0	53.1/42.5	49.6/39.7	58.7/46.9	8.2/10.7	9.9/12.9	M or E	3L	3.3	17.25:1	D	T	7.9	10.2
DE-P60		1103A-33TG2	60.0/48.0	68.1/54.5	66.0/52.8	75.1/60.1	10.4/13.9	12.5/16.6	M or E	3L	3.3	17.25:1	D	T	7.9	10.2
DE-P80		1104A-44TG2	80.0/64.0	91.3/73.0	88.0/70.4	100.3/80.3	14.0/18.7	16.9/22.3	M or E	4L	4.4	17:25.1	D	T	8.0	13.0
DE-P100		1104C-44TAG2	93.0/74.5	109.0/87.0	103.0/82.5	120.0/96.0	16.5/21.8	19.9/25.8	M	6L	5.99	16.0:1	D	T	16.1	27.7
DE-P135		1006A-70TG1	136.0/109.0	151.0/120.5	150.0/120.0	165.5/132.5	24.1/31.5	28.9/37.6	M	6L	5.99	17.0:1	D	TA	19.0	37.2
DE-P150		1006A-70TAG2	150.0/120.0	N.A.	165.0/132.0	N.A.	31.0/41.0	N.A.	M	6L	5.99	17.0:1	D	TA	19.0	41.0
DE-P180		1106A-70TAG3	180.0/144.0	200.0/160.0	200.0/160.0	219.0/175.0	40.2/44.0	36.8/41.3	E	6L	6.6	16.2:1	D	TA	16.5	21.0
DE-P200		1106A-70TAG4	208.0/166.0	231.0/185.0	229.0/183.0	253.0/202.0	35.0/45.2	38.5/51.5	E	6L	8.7	16.9:1	D	TA	26.4	37.2
DE-P250		1506A-E88TAG3	250.0/200.0	N.A.	275.0/220.0	N.A.	36.0/45.0	N.A.	E	6L	8.7	16.9:1	D	TA	26.4	37.2
DE-P300		1506A-E88TAG5	300.0/250.0	N.A.	275.0/220.0	N.A.	36.0/45.0	N.A.	E	6L	8.7	16.9:1	D	TA	26.4	37.2
DE-P350		2206A-E13TAG2	350.0/280.0	400.0/320.0	400.0/320.0	438.0/350.0	54.0/71.0	62.0/81.0	E	6L	12.5	16.3:1	D	TA	40.0	51.4
DE-P400		2206A-E13TAG3	400.0/320.0	400.0/320.0	450.0/360.0	438.0/350.0	62.0/81.0	62.0/81.0	E	6L	12.5	16.3:1	D	TA	40.0	51.4
DE-P450		2506A-E15TAG1	455.0/364.0	500.0/400.0	500.0/500.0	563.0/450.0	72.0/95.0	78.0/102.0	E	6L	15.2	16.0:1	D	TA	62.0	58.0
DE-P500		2506A-E15TAG2	500.0/400.0	500.0/400.0	550.0/440.0	563.0/450.0	76.0/100.0	78.0/102.0	E	6L	15.2	16.0:1	D	TA	62.0	58.0
DE-P600		2806A-E18TAG1	600.0/480.0	625.0/500.0	660.0/528.0	687.0/550.0	90.0/123.0	95.0/127.0	E	6L	18.1	14.5:1	D	TA	62.0	61.0
DE-P650		2806A-E18TAG2	650.0/520.0	625.0/500.0	700.0/560.0	687.0/550.0	97.0/132.0	95.0/127.0	E	6L	18.1	14.5:1	D	TA	62.0	61.0
DE-P750		4006-TAG2A	750.0/600.0	750.0/600.0	825.0/660.0	825.0/660.0	121.0/157.0	129.0/177.0	E	6L	22.92	13.6:1	D	TA	113.4	105.0
DE-P800		4006-TAG3A	800.0/640.0	844.0/675.0	900.0/720.0	938.0/750.0	130.0/172.0	144.0/200.0	E	6L	22.92	13.6:1	D	TA	113.4	105.0
DE-P1000		4008TAG2A	1022.0/818.0	N.A.	1125.0/900.0	N.A.	160.0/220.0	N.A.	E	8L	30.56	13.6:1	D	TA	153.0	143.0
DE-P1250		4012-46TWG2A	1253.0/1002.0	1253.0/1002.0	1385.0/1108.0	1385.0/1108.0	196.0/259.0	N.A./266.0	E	12V	45.84	13.6:1	D	TWC	177.0	196.0
DE-P1350		4012-46TWG3A	1364.0/1092.0	1364.0/1092.0	1500.0/1200.0	1500.0/1200.0	213.0/283.0	N.A./291.0	E	12V	45.84	13.6:1	D	TWC	177.0	196.0
DE-P1500		4012-46TAG2A	1505.0/1204.0	1510.0/1208.0	1656.0/1325.0	1669.0/1329.0	237.0/301.0	195.0/319.0	E	12V	45.84	13.6:1	D	TA	177.0	207.0
DE-P1700		4012-46TAG3A	1710.0/1368.0	1710.0/1368.0	1880.0/1504.0	1880.0/1504.0	275.0/370.0	226.0/361.0	E	12V	45.84	13.6:1	D	TA	177.0	207.0
DE-P2000	4016 TAG2A	2058.0/1646.0	N.A.	2263.0/1811.0	N.A.	397.0/409.0	N.A.	E	16V	61.12	13.6:1	D	TA	237.2	316.0	